

### 10G SFP+ AOC

#### Features

- Electrical interface compliant to SFF-8431
- Hot Pluggable
- 850nm VCSEL Transmitter, PIN photo-detector receiver
- Up to 300m on OM3 MMF
- Operating case temperature: 0°C to 70°C
- All-metal housing for superior EMI performance
- RoHS compliant (lead free)



### 25G SFP28 AOC

#### Features

- Hot-pluggable SFP28 form factor
- Supports 28Gbps data rate
- Maximum link length of 70m on OM3 MMF and 100m on OM4 MMF
- 850nm VCSEL laser and PIN photo-detector
- Internal CDR on both Transmitter and Receiver channel
- Single 3.3V power supply
- Power dissipation < 1W
- Digital diagnostics functions are available via the I2C interface
- RoHS-6 compliant
- Commercial case temperature range: 0°C to 70°C



### 40G QSFP+ AOC

#### Features

- Full duplex 4 channel 850nm parallel active optical cable
- Transmission data rate up to 10.3Gbit/s per channel
- SFF-8436 QSFP+ compliant
- Hot pluggable electrical interface
- Differential AC-coupled high speed data interface
- 4 channels 850nm VCSEL array
- 4 channels PIN photo detector array
- Maximum link length of 300m on OM3 Multimode Fiber (MMF) and 400m on OM4 MMF
- Low power consumption < 1.5W
- Operating case temperature: 0°C to +70°C
- 3.3V power supply voltage
- RoHS 6 compliant



### 40G QSFP+ TO 4X 10G SFP AOC

#### Features

- Electrical interface compliant to QSFP+ connector (SFF-8436) and SFP+ connectors (SFF-8431)
- Hot Pluggable
- 850nm VCSEL transmitter, PIN photo-detector receiver
- Up to 100m on OM3 MMF
- Operating case temperature: 0°C to 70°C
- All-metal housing for superior EMI performance
- RoHS compliant (lead free)



### 100G QSFP28 TO 4X 25G SFP28 AOC

#### Features

- Electrical interface compliant to SFF-8436 and SFF-8431
- Hot Pluggable
- 850nm VCSEL laser and PIN photo-detector
- Maximum link length of 70m on OM3 MMF and 100m on OM4 MMF
- Operating case temperature: 0°C to 70°C
- Internal CDR on both Transmitter and Receiver channel
- Digital diagnostics functions are available via the I2C interface
- All-metal housing for superior EMI performance
- RoHS-6 compliant



## Order On Request

เนื่องจาก สายนอกรีตใช้เชื่อมต่อ ใน Data Center มีความละเอียดอ่อน จึงจำเป็นต้องสอบถามข้อมูลรายละเอียด  
 เกี่ยวกับความถี่ของสายแล้ว บริษัทสามารถเสนอราคาได้ทันที และ สามารถส่งผลิตและส่งสินค้าทันทีได้ภายใน 2 อาทิตย์