



## EN-2826

**Product Name : 2 SFP + 24 RJ45 Adaptive Port Gigabit Managed Switch**

**Model : GNT-2826**

**Network Standard :**

**IEEE802.3 10Base-T, IEEE802.3u 100Base-TX ,**

**IEEE802.3ab 100Base-T , IEEE802.3x ,**

**IEEE802.3ab , IEEE802.3z , IEEE802.1p , IEEE802.1q ,**

**IEEE802.1d , IEEE802.1w , IEEE802.1s**

**Forwarding Mode: Store-and-forward**

**MAC Address Table: Max.8K**

**VLAN: 802.1Q-VLAN (4K), support Voice VLAN, support GVRP,**

**support VLAN VPN (Q-in-Q), support**

**DHCP: DHCP Client / DHCP Relay / DHCP Snooping**

**Port: 24 , 10/100/1000M adaptive RJ45 port 4 , gigabit SFP slot**

**Transmission Medium: Cat3/Cat.5e/Cat6 cable**

**Flow Control: 10/100/1000Mbps**

**Backplane Bandwidth: 52 Gbps**

**LED Light: LINK/ACT , 10/100M , 1000M , PWR , SYS**

**Power Supply: 100~240V , AC , 50/60Hz**

**Size (mm): 440\*180\*45**

**Working Environment: Operating temperature: 0℃~50℃**

**Storage temperature: -40℃~70℃**

**Operating humidity: 10%~90% non-condensing**

**Storage humidity: 5%~90% non-condensing**