



Zircon UPS Seven Dream

Rating	VA	800VA/850VA/1000VA
	WATT	480W/500W/520W
Input	Voltage	220 VAC +/-25%
	Frequency	50/60Hz +/-10% (Auto Sensing)
Output	Voltage	220 VAC +/-10%(AVR), +/-5%(Battery)
	Frequency	50Hz +/-0.1%
	Wave Form	Modified Sine Wave, Simulate Sine Wave
System Protection	System Design	Line Interactive UPS with Stabilizer, Microprocessor Control
	Transfer Time	Typical 2 ms.
	Surge Energy Dissipation	320 Joules (6500A)
	Noise Filter	EMI Suppression
Battery	Overload & Short Circuit	Reset Fuse Protection
	Type	Maintenance Free Sealed Lead-acid Battery
	Battery	ZIRCON 1 x 12V 7.8Ah x 1 Unit
	Recharge Time	4-6 Hours (90% After Fully Discharged)
Indicator	Backup For Computer 1 Set	Backup Time 15-30 Min. (Depend on loads)
	LCD Display	AC Mode, Battery Mode, Input Voltage, Output voltage, Battery Level, Charging Battery, Load Level, Low Battery, Overload, Fault & Battery Replace
Environment	Ambient Temperature	0 to +40 °C
	Audible Noise	< 40db(1 Meter)
	Relative Humidity	90% (Non-Condensing)
	Safety	IEC/EN62040-1;IEC/EN60950-1
Software	Electromagnetic Compatibility	IEC/EN62040-2;IEC61000-4-2;IEC61000-4-3;IEC61000-4-4;IEC61000-4-5; IEC61000-4-6;IEC61000-4-8
	USB Port	Window 2000, 2003, XP, Vista, 2008, 7, Linux, Unix, Max
Standard	Regular Approvals	TISI1291/2553, 2555, ISO9001:2015, ISO14001, CE, FCC, RoHS
Dimensions	WxDxH (mm.)	101x298x142
Weight	Kilogram	4.1 kg /4.2 kg/ 4.5 kg /

- All specifications subject to change without notice.
- Custom-made specifications are acceptable.