

ZN-T1

Body Temperature Detection Network Camera





- On-board temperature-detection algorithm
- Dual lens (Thermal + Visible Light)
- Effective pixels: 320×240
- Thermal sensitivity: $\leq 50\text{mK}$
- Thermal: 8mm fixed lens
- Visible: 2.7-12mm motorized lens
- Accuracy: $\pm 0.3^{\circ}\text{C}$ (must be used with a black body)
- Subject detection (up to 16 targets)
- Response time: $\leq 50\text{ms}$
- 14 color palettes

Specifications

Thermal Camera		Visible Lens	
Thermal Detector	Uncooled IRFPA Microbolometer	Image Sensor	1/2.8" Sony CMOS
Effective Pixels	320(H) * 240(V)	Effective Resolution	1920(H) * 1080(V)
Pixel Size	20um	Shutter Speed	1/50 ~ 1/64,000s
Thermal Sensitivity (NETD)	$\leq 50\text{mK}$ @ F1.0 300K	Wide Dynamic Range	True WDR 120dB
Spectral Range	8 ~ 14um	Min. Illumination	Color: 0.1Lux @(F1.2, AGC ON) B/W: 0.01Lux @(F1.2, AGC ON)
Image Setting	Polarity LUT / DVE / Mirror / FCC / 3D DNR Brightness / Contrast / ROI	S / N Ratio	More than 55dB
Color Mode	Black-Heat / White-Heat / Rainbow / Iron-Red up to 14 modes	Focal Length	2.7 ~ 12mm
Thermal Lens		Max Aperture	F1.6 ~ F2.9
Lens Type	Fixed	FOV	105° ~ 32°
Focus Control	Manual Focus	Focus Control	Motorized
Focal Length	8mm		
Iris	F1.0		
FOV	H: 44°, V: 33°		

Video and Audio		Network	
Compression	H.265, H.264, MJPEG	Ethernet	RJ-45 (10 / 100Base-T)
Frame Rate	Main Stream: Thermal: D1 @25 / 30fps Visible: 1920 * 1080 / 1280 * 720 @25 / 30fps Sub Stream: Thermal: CIF @25 / 30fps Visible: D1 / VGA / 640 * 360 / CIF / QCIF / QVGA @25 / 30fps	Protocol	IPv4 / IPv6, HTTP, RTSP / RTP / RTCP, TCP / UDP, DHCP, DNS, PPPOE, SMTP, SIP, 802.1x
Bit Rate Control	CBR / VBR	Interoperability	ONVIF, CGI, SDK
Bit Rate	Thermal: 100Kbps ~ 6Mbps Visible: Main stream: 200Kbps~12Mbps Sub stream: 10Kbps ~ 6Mbps	Streaming Method	Unicast
Region of Interest	Off / On (8 rectangular zones)	Max. User Access	10 Users
Digital Zoom	16x	Edge Storage	NAS Local PC for instant recording Micro SD card 128GB
Mirror	Support	Web Viewer	<IE11, Chrome, Firefox
Defog	Support	Web Language	English, Chinese, Polish, Italian, Portuguese, Spanish, Russian, French, Czech, Hungarian
Motion Detection	Support	Interface	
Privacy Masking	Off / On (4 rectangular areas)	Ethernet	1 Ethernet (10 / 100 Base-T) RJ-45 Connector
DVE Image Enhancer	Support	Audio	1ch Audio-In, 1ch Audio-Out
Audio Compression	G.711, AMR, RAW_PCM (Optional)	Alarm	2ch Alarm-In, 2ch Alarm-Out
Intelligence		RS485	Support
Alarm	Motion Detection, Disk Alarm, I/O Alarm, Temperature Alarm	BNC Output	N/A
IVS	Smart Body Detection, Perimeter, Single Virtual Fences, Double Virtual Fences, Object Left, Object Removed	Reset Button	Support (Built-in)
Temperature Detection		General	
Detection Mode	Body temperature monitoring	Power Supply	DC12V / POE (IEEE 802.3af)
Detection Preset	Max.16 goals	Power Consumption	Max 10W
Temperature Alarm	Out-of-range temperature alarm, temperature difference alarm	Operating Temperature	-30°C ~ 60°C (-22°F ~ 140°F)
Accuracy	≤0.3°C (Emission rate, distance, ambient temperature, etc.)	Storage Conditions	0 ~ 90% RH
Response Time	≤50ms	Certifications	CE / FCC
Detection Range	-20°C ~ 60°C (-4°F ~ 140°F)	Ingress Protection	IP66
Temperature Display Mode	If temperature difference >5°C, display absolute temperature value; If temperature difference ≤5°C, display relative temperature value (temperature difference DEV = highest value - average)	Casing	Metal
		Dimensions (L*W*H)	212 * 182 * 136 (mm)
		Net Weight	2kg

Dimensions (mm)



Accessories

Optional:



ZN - BK346A
Wall bracket



ZN - BK350
Ceiling Bracket

