

Oxygen Concentrator



8F-3AW Oxygen Concentrator

Flow range: 0-3L/min
 Oxygen concentration: 93% ± 3%
 Maximum Outlet Pressure: 20 ~ 50kPa
 Sound Level: Average (Front Side): 42dB(A), whole unit: 46dB(A).
 Input power: 230VA
 Weight: 11.8kg(25.96 lbs)
 Dimension: W39cm(15.4 ") × D24.5cm(9.7 ") × H50cm(19.7 ")
 Minimum Operating Time: 30minutes



8F-5AW Oxygen Concentrator

-  Global sales leader
-  Medical grade
-  95.5%-87% oxygen concentration
-  5L oxygen flow

Flow Range: 0.5 ~ 5L/min
 Oxygen Concentration: 95.5%-87%
 Maximum Outlet Pressure: 40 ~ 70kPa
 Sound Level: Front side 48dB(A)(average), Whole unit 52dB(A)
 Input Power: 400VA
 Weight: 15.5kg (34.1 lbs)
 Dimension: H50cm(19.7") × W39cm(15.4") × D 24.5cm(9.6")
 Minimum Operating Time: 30minutes



9F-5AW Oxygen Concentrator

Flow range: 0.5 ~ 5L/min
 Oxygen concentration: 93% ± 3%
 Output pressure: 40~70kPa
 Input power: 400VA
 N.W.: 18kg
 Sound level: Front side 49.5 dB(A), whole unit 52 dB(A)
 Size: 50*21*64cm





9F-3BW Oxygen Concentrator

-  Stable Oxygen Concentration
-  Backlight & brightness adjustable LCD screen
-  Ultra Silent
-  Infrared Remote Control System
-  Voice broadcast function
-  U.S. IMPORTED SIEVE

Flow range: 0.5 ~ 3L/min
 Oxygen concentration: 93% ± 3%
 Output pressure: 20~50kPa
 Input power: 230VA
 N.W.: 10.5kg
 Operation noise level: ≤46dB(A)
 Size: 31.5*20*39.5cm



9F-3AW Oxygen Concentrator

Flow range: 0.5 ~ 3L/min
 Oxygen concentration: 93% ± 3%
 Output pressure: 20~50kPa
 Input power: 320VA
 N.W.: 16.5kg
 Operation noise level: ≤46dB(A)
 Size: 50*21*64cm

- High intake position, cleaner air
- Remote control function
- 4 alarm system (Low oxygen concentrator alarm, Power outage alarm, Pressure cycle failure alarm, Compressor failure alarm) , self detection of fault
- 4 safety protection

Oil free pump

- The heart of Oxygen Concentrator
- Compressor adopts with Germany technology
- 30000 hours service life
- 5 years warranty



YU600 Homecare Oxygen Concentrator

Flow range: 1-3L/min
 Oxygen concentration: 70%-90%
 Input power: 150VA
 N.W.: 8kg
 Operation noise level: 45dB(A)
 Size: 31.7*19*37.7(cm)



YU300 / YU500 Homecare Oxygen Concentrator

Flow range: 1 ~ 5L/min
 Oxygen concentration: 30%~90%
 Input power: 100VA
 N.W.: 7.5kg
 Operation noise level: 43dB(A)
 Size: 27cm*17.5cm*29.5cm

9F-3/ 9F-3W Oxygen Concentrator

-  Low oxygen concentrator alarm
-  Pressure cycle failure alarm
-  Power outage alarm
-  Compressor failure alarm

Flow range: 0.5 ~ 3L/min
 Oxygen concentration: 93% ± 3%
 Output pressure: 20~50kPa
 Input power: 320VA
 N.W.: 15.5kg
 Operation noise level: 45-46dB(A)
 Size: 50*21*64cm



7F-3 / 7F-3W

Technical data:
 Flow range: 0.5 ~ 3L/min
 Oxygen concentration: 93% ± 3%
 Output pressure: 20~50kPa
 Pressure relief mechanism operational at: 250kPa ± 25kPa
 Operation noise level: ≤55dB (A)
 Input power: 320VA
 Minimum operating time: 30minutes

FEATURES:
 Complete plastic out shell, safe and reliable.
 Timing turn off function allows convenience use.
 Quality press safety valve ensures better security.
 Installed power cut warning function.
 Compressor with heat protection which ensure safe of the compressor and concentrator.
 Power cord and nasal oxygen cannula etc. accessories can be put in the store box.
 Can be connected with nebulizer to have nebulizing cure.



- Power supply of the oxygen concentrator:
 AC120V ± 10% AC220V ± 10% AC230V ± 10% 50Hz 60Hz



7F-3E / 7F-3EW

Technical data:
 Flow range: 0.5~3L/min
 Oxygen concentration: 93% ± 3%
 Output pressure: 20~50kPa
 Input power: 380VA
 Operation noise level: ≤50dB (A)

Positive intake, air cleaner, molecular sieve life longer
 More function:
 With time accumulating function, timing power off function,
 fault self-detection system.
 Four alarm functions:
 Power failure alarm
 Low oxygen concentration alarm
 Pressure cycle failure alarm
 Compressor failure alarm



7F-3B / 7F-3BW



7F-3D / 7F-3DW

7F-3A / 7F-3AW / 7F-5A / 7F-5AW

Technical data:
 Flow Range: 0.5~3L/min, 0.5~5L/min
 Oxygen Concentration:
 93% ± 3%(7F-3A/3AW); 95.5%~87% (7F-5A/7F-5AW)
 Noise: ≤50dB(7F-3A/3AW); ≤53dB(7F-5A/5AW)
 Input power: 320VA(7F-3A/3AW); 400VA(7F-5A/5AW)

More function:
 With time accumulating function, timing power off function
 Fault self-detection system.
 Four alarm functions:
 Power failure alarm
 Low oxygen concentration alarm
 Pressure cycle failure alarm
 Compressor failure alarm



- Oxygen concentrator (with nebulizer function) provided by yuwell uses the combination of oxygen uptake and atomization function to offer clean and safe air. Furthermore it's a multifunctional machine that also assist in atomized treatment while maintaining the same oxygen concentration.



7F-5 / 7F-5W

Technical data:
 Oxygen flow: 0.5 ~ 5L/min
 Oxygen concentration: 95.5%~87%
 Output pressure: 40~70kPa
 Pressure relief mechanism operational at: 250kPa ± 25kPa
 Operation noise level: ≤53dB(A)
 Input power: 500VA
 Minimum operating time: 30minutes

FEATURES:
 Complete plastic outer shell, safe and reliable.
 Timing accumulating function, showing total working hours through the display screen.
 Press safety valve help ensure better security.
 Power failure alarming function, high pressure and low pressure alarming function.
 Compressor has got heat protection that ensures the safety of the compressor and concentrator.
 Having nebulizing interface optional.
 May connect with nebulizer to have nebulizing cure.

Colors currently available:
 Beige, Black

7F-8 / 7F-8W

Flow range: 0.5 ~ 8L/min
 Oxygen concentration: 95.5%~87%
 Output pressure: 40~70kPa
 Pressure relief mechanism operates at: 250kPa ± 25kPa
 Operation noise level: ≤55dB(A)
 Input power: 500VA

7F-10 / 7F-10W

Flow range: 0.5 ~ 10L/min
 Oxygen concentration: 95.5% ~ 87%
 Output pressure: 40~70kPa
 Pressure relief mechanism operational at: 250kPa ± 25kPa
 Operation noise level: ≤60dB(A)
 Input power: 850VA
 Minimum operating time: 30minutes

- The "W" behind the item name means with nebulizing function, we can adapting nebulizer function to every oxygen concentrator, except the 1L machine.

7F-5 Double flux / with cord controller



Oxygen Bag



Model: SY-30L, SY-42L

The oxygen bag is made with non-toxic and safe pvc, mainly used for emergency in hospital and health care product at home. Clean, safe, durable and easy to carry.
 G.W./N.W.: 9/7.1kgs
 Packing: 20PC/CTN 50*24*30cm



7F-5 MINI

Yuwell provide you with the following oxygen uptake methods:
 Nasal cannula oxygen uptake
 Mask type oxygen uptake
 Headset type oxygen uptake



Nasal cannula

The nasal cannula provided is 2m long, length customization available upon requests.



Headset type



Mask type

More portable and takes up less space

You may also choose the color preferred:
 white, black, silver.

- Maximum Nebulizing Rate of 3L machine: ≥0.15mL/min
 Maximum Nebulizing Rate of 5L machine: ≥0.2mL/min