

# Tiandy



## TC-R3432 Spec: I/B/K/V3.1

# H.265 4HDD 32ch NVR

Lite-K Series



## KEY FEATURES

### HD Input

- S+265/H.265/H.264 video formats
- Connectable to the third-party network cameras
- Up to 32-channel input
- Supports live view, storage, and playback of the connected camera at up to 8MP resolution

### HD Output

- HDMI and VGA simultaneous output
- HDMI Video output at up to 4K (3840×2160) resolution

### HD Storage

- 4 SATA interfaces, up to 10TB for each HDD
- S+265 compression effectively reduces the storage space and costs by up to 75%

### HD Transmission

- 2×RJ45 self-adaptive 10/100/1000 Mbps network interfaces

### Various Applications

- Centralized management of IP cameras, including configuration, information import/export, real-time information display, upgrade, etc.
- Connectable to smart IP cameras from Tiandy and the recording, playing back, and backing up of VCA alarms can be realized
- VCA detection alarm is supported
- Smart search for the selected area in the video and smart playback to improve the playback efficiency
- Web6 supports plug-in free browsing and can preview videos on all browsers
- Support cloud upgrade




## SPECIFICATIONS

Input	
Video Input	32-ch
Max Resolution	8MP
Two-way Audio Input	1-ch, 3.5mm
Bandwidth	Income 160Mbps; Outgoing 48Mbps
Output	
HDMI/VGA Output	HDMI 1-ch, 3840×2160, 2560×1440, 1920×1080, 1280×720, 1024×768, 1440×900, 1280×800 VGA 1-ch, 1920×1080, 1280×720, 1024×768, 1440×900, 1280×800
Screen Split	1/3/4/6/8/9/10/13/16/20/25/32
Audio Output	1*RCA
Decoding	
Decoding Format	S+265/H.265/H.264
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Preview Capability	2×8MP, 2×6MP, 3×5MP, 4×4MP, 5×3MP, 8×1080P, 16×720P, 32×4CIF
Synchronous Playback	2×8MP, 2×6MP, 3×5MP, 4×4MP, 5×3MP, 8×1080P, 16×720P
Records Encryption	Yes
Hard Disk	
SATA	4 SATA interfaces for 4 HDDs
Capacity	Up to 10TB for each HDD
eSATA Interface	N/A
Array Type	JBOD, RAID0/1/5/6/10
External Interface	
Network Interface	1×RJ45 self-adaptive 10/100/1000 Mbps network interfaces
USB Interface	2×USB 2.0
Serial Interface	N/A
Alarm In/Out	N/A
Network	
Protocol	TCP/IP, UDP, IPV4, IPV6, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTCP, RTMP, FTP, NFS, PPPoE, NTP, UPnP, SMTP, IGMP, Multicast, ARP, SNMP, SSL, SSH
System Compatibility	ONVIF (PROFILE S/T/G), SDK, P2P
General	
Web Version	Web6
Language	Simple Chinese, Traditional Chinese, English, Spanish, Korean, Italian, Turkish, Russian, Thai, French, Polish, Dutch, Hebraism, Arabic
Operating Conditions	-10°C ~ 55°C, 10%~90% RH
Power Supply	100~240V AC, 50~60 Hz
Consumption (without HDD)	≤25W (without HDD)
Chassis	1.5U
Dimensions	75×347×440mm, (2.95×13.66×17.32 inch)
Weight (without HDD)	3.35Kg (7.38lb)


## AVAILABLE MODEL

**TC-R3432 SPEC: I/B/K/V3.1**

## DIMENSIONS (Unit: mm)



## Physical Interfaces



DISTRIBUTED BY



**Tiandy Technologies Co.,Ltd.**

Email: [sales@tiandy.com](mailto:sales@tiandy.com)  
Website: [en.tiandy.com](http://en.tiandy.com)

Tel: +86-22-58596178  
Fax: +86-22-58596048