

# Outdoor Full-Color

PT Network Camera

MODEL: VIGI C540



Smart Detection



Powerful Pan Tilt



IP66



On-Board Storage



Two-Way Audio

## // Smart Detection

Receive notifications and check feeds when someone crosses a boundary, enters an area you've set, or obstructs the camera.




### **Motion Detection**

Get instant notifications when your camera detects motion.




### **Human Detection**

Smarter security alerts focus on human movement instead of flying insects, small animals and leaves.



### **Line-Crossing**

Set a boundary and receive an alert anytime a person crosses it from either or both directions.



### **Area Intrusion**

Set customized activity zones around key areas for more focused monitoring.



### **Camera Tampering**

Receive alerts when someone obstructs the camera.

## // SmartVid



### **Smart IR**

Keeps objects from being under-rendered when far away or overexposed when close to camera at night.



### **Wide Dynamic Range**

Adjusts for lighting contrast to minimize shadowing effects and renders images true to life.



### **3D DNR**

Removes abnormal pixelation to provide clearer video and eliminate distortion.


## // Flexible Pan Tilt

- Scheduled Movement
- Auto Tracking
- Power-off Memory Function
- Remote Monitoring & Configuration

## // VIGI Surveillance Solution


The VIGI professional surveillance system by TP-Link is dedicated to protecting the business that you've worked hard to build—whenever, wherever.

Outstanding functions, reliable quality guarantees, and simplified installation work together to ensure your business stays safe and sound.



## // Flexible Installation

Find the perfect vantage point by simply securing your camera to the ceiling, wall, or pole.



## // Specifications

Camera	
Image Sensor	1/3" Progressive Scan CMOS
Day & Night	IR Cut Filter
Digital Noise Reduction	3D DNR
WDR	DWDR
PTZ	
Pan/Tilt Range	Pan: 0° to 350°, Tilt: 0° to 120°
Zoom	Yes
Lens	
Lens Type	Fixed focal lens, 4mm
Aperture	4 mm: F1.6
Focal Length & FOV	4mm Horizontal FOV: 79°, Vertical FOV: 43°, Diagonal FOV: 93°
Lens Mount	M12
Illuminator	
IR LED	Range: 30m; Wavelength: 850nm
White LED	Range: 30m
Compression Standard	
Video Compression	Main stream: H.265/H.264 Sub-Stream: H.265/H.264
H.264 Type	Main Profile/High Profile
H.264+	Main Stream Supported
H.265 Type	Main Profile
H.265+	Main Stream Supported
Video Bit Rate	Main Stream: 256 Kbps to 4 Mbps Sub-Stream: 64 Kbps to 512 Kbps
Smart Feature-set	
Smart Event	Area Intrusion Detection, Line-Crossing Detection, Human Detection

Basic Event	Motion Detection, Video Tampering Detection, Exception ( Illegal login)
Linkage Method	Trigger Notification: ONVIF, HTTPS
Region of Interest	1 Region
<b>Image</b>	
Max. Resolution	4MP
Main Stream	Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 2560x1440, 2304x1296, 2048x1280, 1920x1080
Sub-Stream	Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 640x480, 352x288, 320x240
Image Enhancement	BLC/3D DNR/Prevent Overexposure to Infrared Light
Image Settings	Mirror, Brightness, Contrast, Saturation, Sharpness, Exposure, WDR, White Balance Adjustable by Client Software
Day/Night Switch	Day/Night/Auto/Schedule
<b>Network</b>	
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP, UDP, SSL/TLS
General Function	Two Streams, Mirror, Privacy Masks, Password Reset via E-mail, HTTP Listening
API	ONVIF
Security	Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication
Simultaneous Live View	3 Main Streams & 3 Sub-Streams
User/Host	Up to 21 Users
Client	VIGI Security Manager, VIGI app
<b>Interface</b>	
Communication Interface	1 RJ45 10/100M Self-Adaptive Ethernet Port
Video Output	No
Reset Button	Yes

On-board Storage	Built-In Memory Card Slot, Support MicroSD Card, Up to 256 GB
Built-in Speaker	Yes
Built-in Microphone	Yes
<b>General</b>	
Operating Temperature	-30–60 °C
Power Supply	12V DC ± 5%, 5.5mm Coaxial Power Plug PoE (802.3at, class 4)
Power Consumption	12V DC: Max 14W PoE: Class 4
Material	Plastic
Product Dimensions	120 × 172 × 198 mm
Certifications	CE, RCM, BSMI, VCCI, RoHS, KC

Specifications are subject to change without notice and can be found at [www.tp-link.com](http://www.tp-link.com).

©2022 TP-Link