

Specifications Model: CS55

| | | |
|-------------------------------|------------------------|--|
| System | Operation system | Embedded Linux OS |
| | Online visitor | Support 4 visitors at the same time |
| Image Capture | Image sensor | 1/2.9 inch 1080p Progressive Scan CMOS |
| | Minimum Illumination | 0.3~0.5Lux(color mode),0Lux(B&W mode) |
| | Lens/View Angle | 4mm@F2.0/101°(Diagonal) |
| | Nightvision | Dual Filter,IR-Cut, 18pcs 850nm patch IR LED, IR irradiation distance:15m |
| Video | Encode format | H.264 main profile/Motion-JPEG/JPEG |
| | Streams | Main stream: 1080p(1920×1080)@30fps/1296p(2304×1296)@30fps Substream: 360p(640×360)@15fps |
| | Bit Rate/Max Fps | 128~4096kbps/30pfs |
| | Image adjustment | Brightness and contrast can be adjusted |
| Audio | Input | Built-in -38db microphone |
| Network | Ethernet | 10Base-T / 100Base-TX, RJ45 connector |
| | Protocols | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P etc |
| | Wireless LAN | IEEE802.11b/g/n, Supports AP mode |
| | Wireless LAN Frequency | 2.4~ 2.4835GHz |
| | Wireless LAN security | 64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption |
| Memory | Socket | TF Push-push socket,(support maximum 256GB); Cloud Storage; NVR; NAS |
| Alarm | Alarm Trigger | Motion detection, Humanoid detection, Crying detection, Electronic fence |
| Physical Environmental | Rated voltage | DC12V±5% |
| | Power consumption | Related power:6W |
| | Operating condition | Temperature:-10~50℃,humidity:<90% |
| | Weight | Net: 230g Gross: 450 g (Note: in kind prevail) |
| | Package size | 265x130x85 mm (L×W×H) |