

RG-ES228GS-LP

28-Port Gigabit Smart Cloud Managed PoE Switch



Highlights

- 28-port gigabit cloud managed switch with 24 PoE+ ports
- Cost-effective smart cloud managed switch
- IP Camera Recognition, unique value for CCTV network
- Automatic Loop Prevention, ensuring service continuity
- Lifetime management on Ruijie Cloud at anytime, anywhere

Highlight Features

RG-ES200 Series Switches

Gigabit access switch fits the needs in SMB network



802.3at / 802.3af




Abundant Application Scenarios



Centralized Cloud Management

Cost-Effective Smart Cloud Managed Switches

ES200 adopts a light-weighted Cloud management design, providing faster response to support richer features.



IP Camera/NVR
recognition



Automatic
Loop Prevention




Mobile VLAN
Configuration



Intelligent
PoE Adaptive


Highlight Features

Unique Value for CCTV Network



Automatic Loop Prevention Ensures Service Continuity

Network stays connected when network loop happens



Highlight Features

Cloud, Make Your Business Easy

- SON, zero touch provisioning to Cloud
- Configure VLANs on Ruijie Cloud APP
- Monitor switch statistics at anytime anywhere
- Easy maintenance, save onsite time and cost



Product Information

Model	RG-ES228GS-LP
Product Category	Layer 2

Hardware Specifications

Model	RG-ES228GS-LP
Power Supply and Consumption	
PoE Out standard	PoE/PoE+ (IEEE 802.3af/at)
Number of PoE Out ports	24
Number of PoE/PoE+ Out ports	24
PoE budget	250W
PoE power pins	1-2 (+), 3-6 (-)
Power input	220 V AC power supply: • Rated input voltage: 100 V AC to 240 V AC, 50 Hz to 60 Hz • Maximum input voltage: 90 V AC to 264 V AC, 47 Hz to 63 Hz • Rated input current: 6 A
Maximum power consumption	Less than 21W with no PoE load (110V) Less than 20W with no PoE load (220V) Less than 302W with PoE full load (110V) Less than 294W with PoE full load (220V)
Power supply	Fixed power supply
System Specifications	

Hardware Specifications

Model	RG-ES228GS-LP
Flash memory	8 MB
Forwarding rate	41.664 Mpps
Switching capacity	56 Gbps(bit/s)
Environment and Reliability	
Fan	1 x fixed fan
Cooling	Air cooling, front-to-rear airflow
Acoustic noise	< 40 dB: 25°C (77°F)
Mounting options	Desk/Rack
Hot swapping of cables	Hot swapping supported by the service port and power connector
MTBF	200,000 hours
Operating temperature	0°C to 40°C (32°F to 104°F)
Storage temperature	–40°C to +70°C (–40°F to +158°F)
Operating humidity	10% RH to 90% RH (non-condensing)
Storage humidity	5% RH to 95% RH (non-condensing)
Altitude	–500 m to +5,000 m (–1,640.42 ft. to +16,404.20 ft.)
ESD protection	Air discharge: 8 kV Contact discharge: 6 kV
Surge protection	Service port: ±6 kV for common mode Power connector: ±6 kV for common mode and ±6 kV for differential mode

Hardware Specifications

Model	RG-ES228GS-LP
Dimensions and Weight	
Casing	Metal
Product dimensions (W x D x H)	440 mm x 214.9 mm x 43.2 mm (17.32 in. x 8.46 in. x 1.70 in.)
Weight	2.80 kg (4.63 lbs) (without packaging materials)
	3.85 kg (6.83 lbs) (with packaging materials)
Shipping weight	3.85kg (8.12 lbs)
Port Specifications	
Total number of RJ45 ports	26
Total number of optical ports	2
Number of 1GE SFP ports	2
Number of 10/100/1000BASE-T ports	26
Reset button	1
Product Information	
Warranty	3 years
Certification and Regulatory Compliance	
EMC	EN 55032
	EN 61000-3-2
	EN 61000-3-3
	EN 55035
	EN 300 386
Safety compliance	EN 62638-1

Hardware Specifications

Model	RG-ES228GS-LP
Certification	CE, CB

Software Specifications

Model	RG-ES228GS-LP
Authentication	
RADIUS	No
802.1X authentication	No
Basic Configurations	
PoE watchdog	Yes
Uninterruptible power supply upon warm start	No
Online upgrade	Yes
Gateway Features	
802.1p priority-based traffic classification	No
DSCP priority-based traffic classification	No
Network Management and Monitoring	
Fan speed adjustment	Automatic speed adjustment
Mirroring	Yes
HTTP login	Yes
HTTPS login	Yes
SON	Yes
Syslog	No
Camera detection	Yes

Software Specifications

Model	RG-ES228GS-LP
eWeb management	Yes
Ruijie Cloud management	Yes
Ruijie Reyee App management	Yes
SNMPv1, v2c, and v3	No
Security	
Port isolation	Yes
Broadcast storm control	Yes
Multicast storm control	Yes
Unknown unicast storm control	Yes
DHCP snooping	Yes
Standard ACL	No
Extended MAC ACL	No
Extended IP ACL	No
IPv6 ACL	No
ARP anti-spoofing	No
CPU Protection Policy	Yes
IP Service	
ARP	No
IPv4 ping	No
IPv4 traceroute	No
ICMPv6	No

Software Specifications

Model	RG-ES228GS-LP
IPv6 ping	No
IPv6 traceroute	No
DNS client	Yes
DHCP client	Yes
Ethernet Switching	
Maximum number of VLANs	16
Maximum number of MAC address entries	8000
Interface flow control	Yes
IEEE 802.1Q VLAN	Yes
VLAN configuration supported on LAN ports	Yes
LLDP	No
LLDP-MED	No
Static MAC address	Yes
Static aggregation	No
LACP	No
Inbound or outbound rate limiting based on interface traffic	Yes
Interface	
Jumbo frame length (MTU)	10000 bytes

Software Specifications

Model	RG-ES228GS-LP
EEE	Yes
Cable test	Yes
IP Routing	
IPv4 static route	No
IPv6 static route	No
OSPFv2	No
OSPFv3	No
Multicast	
IGMPv1 snooping	No
IGMPv2 snooping	No
Basic IGMPv3 snooping	No
Full IGMPv3 snooping	No
IGMP filtering	No
IGMPv1, v2, and v3	No
System Performance Capacity	
Recommended camera limit	200W H265: 80
	400W H265: 40

Package Contents

Model	RG-ES228GS-LP
Device	
Device	1
Accessories	
Rubber pad	4
Power cord retention clip	1
Screw	6 X M4 x 8 mm cross recessed countersunk head screws
Power cord	1 x 1.8 m (5.91 ft.)
Rack-mount bracket	2
Manual	
User Manual	1
Warranty Card	1

Ruijie | ReYee

 **R**edefine your **e**asy network



Ruijie Networks Co., Ltd.

Official Website: <https://Reyee.Ruijie.com>