



TC-R3840 Spec:I/B/N/V4.0

8HDD 40ch NVR

Pro Series



KEY FEATURES

- Up to 40-ch IP camera accesses
- Incoming/Outgoing bandwidth: 640Mbps/320Mbps
- S+265, H.265, S+264, H.264 video formats
- Max. decoding capability: 16MP(30fps)×3 or 1080P(30fps)×24
- 16-ch synchronous playback
- Up to 24 TB capacity for each HDD
- Simultaneous HDMI1 and VGA1 outputs; Simultaneous HDMI2 and VGA2 outputs
- HDMI output at up to 4K resolution
- 2×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
- S+ 265 compression effectively reduces the storage space by up to 75%
- Support cloud upgrade


SPECIFICATIONS

Video and Audio	
Access Channel	40
Incoming Bandwidth	640Mbps
Outgoing Bandwidth	320Mbps
Resolution	16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Preview Decoding Capability	16MP(30fps)×3, 12MP(30fps)×4, 8MP(30fps)×6, 6MP(30fps)×8, 5MP(30fps)×9, 4MP(30fps)×12, 3MP(30fps)×16, 1080P(30fps)×24, 720P(30fps)×40, 4CIF(30fps)×40
Playback Decoding Capability	16MP(30fps)×3, 12MP(30fps)×4, 8MP(30fps)×6, 6MP(30fps)×8, 5MP(30fps)×9, 4MP(30fps)×12, 3MP(30fps)×16, 1080P(30fps)×16, 720P(30fps)×16, 4CIF(30fps)×16
Third-party Camera Access	ONVIF(Profile S/T); RTSP
HDMI Output	HDMI: 800×600(60Hz), 1024×768(60Hz), 1280×720(50Hz/60Hz), 1280×800(60Hz), 1366×768(60Hz), 1440×900(60Hz), 1920×1080(50Hz/60Hz), 2560×1440(30Hz/60Hz), 2560×1600(60Hz), (4K)3840×2160(30Hz/60Hz)
VGA Output	VGA: 800×600(60Hz), 1024×768(60Hz), 1280×720(50Hz/60Hz), 1280×800(60Hz), 1366×768(60Hz), 1440×900(60Hz), 1920×1080(50Hz/60Hz)
Multi-screen Display	Independent Output: HDMI1/VGA1: 1/2/3/4/5/6/7/8/9/10/12/13/16/20A/20B/25/32/36/40 HDMI2/VGA2: 1/2/3/4/5/6/7/8/9/10/12/13/16/20A/20B/25/32/36/40
Audio Input	1-ch, 3.5mm
Audio Output	1-ch, 3.5mm; BNC
Two-Way Audio	1-ch, 3.5mm, using the audio input
Compression Standard	
Video Compression	S+265; H.265; S+264; H.264
Audio Compression	G.711A; G.711U; AAC; ADPCM_D
Stream Type	Video; Video & Audio
Network	
Network Protocol	802.1X; ARP; DDNS; DHCP; DNS; Easy DDNS; FTP; HTTP; HTTPS; ICMP; IGMP; IPv4; IPv6; Multicast; NFS; NTP; PPPoE; QoS; RTCP; RTP; RTSP; SMB/CIFS; SMTP; SNMP v1/v2/v3; SRTP; SSH; SSL; TLSv1.2; TCP; UDP; Unicast; UPnP
Mobile Client	EasyLive Plus (Android, iOS)
System Compatibility	ONVIF(Profile S/T/G); RTSP; CGI; SDK; P2P
Web	IE10+; Firefox52+; Edge89+; Safari11+; Chrome57+
Recording Playback	
Multi-channel Playback	16
Record Mode	Manual Recording; Alarm Recording; Schedule Recording
Storage Method	Local HDD, eSATA
Backup	USB storage device, eSATA, Network
Playback Function	Play/Pause/Stop/Reverse/Slow/Speed/Backwards 30s/Forwards 30s/Full Screen/Backup (Video Editing)/Step/Digital Zoom/Instant Replay

Dual Stream Record	Yes
Alarm	
General Alarm	Motion Detection; Mask Alarm; Alarm Input(IPC); Alarm Input(NVR)
Exceptions Alarm	Video Loss; Network Disconnected; No Disk; Illegal Access; Disk group space alert; Disk Full; Disk R/W Error; Recording Abnormal; Abnormal found in smart of disk; Abnormal temperature of the disk; Hot-spare Exception; Array Exception; Voltage Alarm(IPC); RTC Failure; IP Address Conflict; MAC Address Conflict; Disk Overload
Intelligent Analytics	
AI by Camera	Tripwire; Double Tripwire; Perimeter; Object Abandon; Object Missing; Running; Parking; Heatmap; Loitering; Video Abnormal; Audio Abnormal; License Plate Recognition; On Duty Detection; Crowd Detection; Safety Helmet Detection; Electric Bicycle Detection; People Counting; Link to Tracking; Smoke and Fire Detection; Environmental Temperature Measurement; Face Detection; Human Body Temperature Measurement; Smart Alarm; Face Recognition; Human/Vehicle Classification
VCA Search	Early-warning Search; Behavior Search; License Plate Search; Safety Helmet Search; Thermographic Retrieval; Duty Search; Electric Bicycle Retrieval; Face Search(Search by face attributes/event)
VCA Report	Heatmap; People Counting; Face Statistics
Face Detection	
Face Attributes Search	Gender; Age; Glasses; Face Mask; Body Temp.
Face Recognition	
Face Picture Library	Up to 300 face libraries Up to 100000 base images
Face Picture Comparison	Yes (Cooperate with facial recognition IPC)
Storage	
HDD Capacity	Up to 24 TB capacity for each HDD
Disk Group	8 Disk Group
RAID	JBOD, RAID0, RAID1, RAID5, RAID6, RAID10 (To enable RAID, please use surveillance-grade AI disks or enterprise-class disks.)
External Port	
eSATA	1×eSATA
USB	2×USB2.0; 1×USB3.0
HDMI	2×HDMI(supports up to 4K resolution output)
VGA	2×VGA
Network Interface	2×RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
SATA	8×SATA interface
RS-232	1×RS-232
RS-485	2×RS-485
Alarm I/O	16-ch, TTL inputs, 3mA, 3.3VDC; 4-ch, relay outputs, 1A, 24VDC
General	
UI Language	Simple Chinese; Traditional Chinese; English; Spanish; Korean; Italian; Turkish; Russian; Thai; French; Polish; Dutch; Hebrew; Arabic; Vietnamese; German; Ukrainian; Portuguese; Albanian; Indonesian; Greek

Power Supply	100~240V AC
Power Consumption	<18W(HDD not included, idling)
NetWeight	6.2Kg
GrossWeight	8.4Kg
Boundary Dimensions	440(L)455(W)94(H)mm
Package Dimensions	565(L)565(W)220(H)mm
Operating Temperature	-10°C~+55°C (+14°F~+131°F)
Operating Humidity	10%~90%RH (non-condensing)
Storage Temperature	-20°C~+60°C (-4°F~+140°F)
Package Kit	Network Video Recorder*1; Screw Pack*1; Mouse*1; European Standard Power Cord*1; Ear Plate*2; SATA Hard Disk Data Cable*8; Instructions*1; Parts List*1

DIMENSIONS (Unit: mm)



Physical Interfaces

