

RG-EW1800GX PRO

AX1800 Wi-Fi 6 Dual-band Gigabit Mesh Router



Highlights

- Unprecedented wireless experience with Wi-Fi 6
- Wi-Fi 6 ultra-high-speed
- Strong signals received
- Exclusive Reyee mesh providing full-space-coverage Wi-Fi solution
- Multi-user support
- Control of your home network at your fingertips

/ Highlight Features

RG-EW1800GX PRO

An Unprecedented Wireless Experience in WiFi 6

All-round upgrade of Wi-Fi performance,
Improve the overall networking experience for users.



5 Gigabit
Ethernet ports



1800M
Dual-band



802.11ax



Enter the Era of Wi-Fi 6 Speed


With 1024-QAM and the latest 802.11ax standard,
the 1800GX PRO delivers a dual-band concurrent transmission rate of up to 1800Mbps,
providing consistent **high-speed** internet experience.



Highlight Features

Strong Signal Received, Feels like “wall-less”

Beamforming technology and built-in signal amplifiers combine to enhance strong Wi-Fi signal throughout your home.



* The data is supported by Tolly Test under the laboratory condition.

Seamless Roaming, Full Space Coverage Wi-Fi Solutions

Amazed by **Reyee Mesh**



Highlight Features


Born For Multi-user

Upgraded **MU-MIMO** version provides 2.5x greater capacity to connect more terminals.
New-Gen tech "**BSS coloring**", Smart anti-interference from nearby Wi-Fi signals.





Take Control of Your Home Network at Fingertips

Set up your home network in **Reyee Router App** in two minutes. More **Life-time Free** functions are waiting for you to Explore, Experience, Expect.



Remote Management Parental Control Smart Home



Hardware Specifications

Model	RG-EW1800GX PRO
Environment and Reliability	
Operating humidity	5% RH to 95% RH (non-condensing)
Operating temperature	-10 °C to +45 °C (14 °F to 113 °F)
Storage humidity	5% RH to 95% RH (non-condensing)
Storage temperature	-40 °C to +70 °C (-40 °F to 158 °F)
Power Supply and Consumption	
Power supply	DC 12 V 1.5 A
Certification and Regulatory Compliance	
Certification	CE
Product Information	
Warranty	3 years
Dimensions and Weight	
Product dimensions (W x D x H)	180 mm × 180 mm × 30 mm (7.09 in. × 7.09 in. × 1.18 in.) (excluding antennas)
Weight	0.55 kg (1.21 lbs) (without packaging materials) 1.15 kg (2.54 lbs) (with packaging materials)
Antenna	
Antenna	4 x external omnidirectional antennas
Antenna gain (2.4 GHz)	4.5 dBi
Antenna gain (5 GHz)	6 dBi
System Specifications	

Hardware Specifications

Model	RG-EW1800GX PRO
RAM	256 MB
Port Specifications	
LEDs	1 x system status LED 1 x Mesh LED 5 x Ethernet port LEDs
LAN ports	4 x 10/100/1000BASE-T ports
WAN ports	1 x 10/100/1000BASE-T port
Wi-Fi Radio	
Operating band	IEEE 802.11b/g/n/ax, 2.400GHz~2.4835GHz; IEEE 802.11a/n/ac/ax, 5.150GHz~5.350GHz; IEEE 802.11a/n/ac/ax, 5.470GHz~5.725GHz; IEEE 802.11a/n/ac/ax, 5.725GHz~5.850GHz;
FEM	EPA
Max. Wi-Fi Speed	2.4 GHz, 573 Mbps 5 GHz, 1200 Mbps
Maximum transmit power	2.4 GHz: 802.11b: 25 dBm 802.11g: 6 Mbps 25 dBm; 54 Mbps 21 dBm 802.11n: MCS0 25 dBm; MCS7 21 dBm 802.11ax: MCS11 19 dBm 5 GHz:

Hardware Specifications

Model	RG-EW1800GX PRO
	802.11a: 6 Mbps 25 dBm; 54 Mbps 21 dBm 802.11n: MCS0 25 dBm; MCS7 21 dBm 802.11ac: MCS0 25 dBm; MCS9 20 dBm 802.11ax: MCS0 25 dBm; MCS9 20 dBm; MCS11 18 dBm Note: The transmit power varies according to regulations in different countries and regions.
Maximum transmit power(EIRP)	Frequency bands using and the max EIRP: Note: Country specific restrictions apply European Union & United Kingdom: 2400-2483.5 MHz, EIRP $\leq$ 20 dBm 5150-5350 MHz, EIRP $\leq$ 23 dBm 5470-5725 MHz, EIRP $\leq$ 30 dBm Myanmar: 2400-2483.5 MHz, EIRP $\leq$ 23 dBm 5725-5825 MHz, EIRP $\leq$ 30 dBm Thailand: 2400-2483.5 MHz, EIRP $\leq$ 20 dBm 5150-5350 MHz, EIRP $\leq$ 23 dBm 5470-5725 MHz, EIRP $\leq$ 30 dBm 5725-5825 MHz, EIRP $\leq$ 30 dBm Indonesia:

Hardware Specifications

Model	RG-EW1800GX PRO
	2400-2483.5 MHz, EIRP $\leq$ 27 dBm 5150-5350 MHz, EIRP $\leq$ 23 dBm 5725-5825 MHz, EIRP $\leq$ 23 dBm Egypt: 2400-2483.5 MHz, EIRP $\leq$ 20 dBm 5150-5350 MHz, EIRP $\leq$ 23 dBm Vietnam: 2400-2483.5 MHz, EIRP $\leq$ 23 dBm 5150-5350 MHz, EIRP $\leq$ 23 dBm 5470-5725 MHz, EIRP $\leq$ 30 dBm 5725-5825 MHz, EIRP $\leq$ 30 dBm
MIMO	2.4 GHz, 2 x 2 5 GHz, 2 x 2
Wi-Fi standard	Wi-Fi 6 (IEEE 802.11ax)
Highest QAM order	1024
2.4 GHz channel width	Auto/20/40 MHz
5 GHz channel width	Auto/20/40/80 MHz

Software Specifications

Model	RG-EW1800GX PRO
Basic Configurations	
LED management	Yes
Internet access mode	PPPoE, DHCP, Static IP, WISP, L2TP
Preconfiguration	Yes
Reset and keep configurations	Yes
Restoring factory defaults	Yes
Configuration backup	Yes
Local upgrade	Yes
Online upgrade	Yes
Scheduled upgrade	No
Disabling the physical Reset button	No
Connectivity detection configuration	Yes
AP mode	Yes
IP Service	
Port mapping	Yes
ARP binding	Yes
Number of ARP binding entries	64
DDNS	Yes
No-IP DNS	Yes
Ruijie DDNS	Yes
NAT-DMZ	Yes

Software Specifications

Model	RG-EW1800GX PRO
Number of port mapping entries	50
UPnP	Yes
IPv6	Yes
Ethernet Switching	
WAN port aggregation	No
LAN port aggregation	No
Specifying the VLAN tag	Yes
Behavior Management	
Parental control	Yes
Client access control (based on MAC addresses)	Yes
Client access control (based on time)	Yes
Maximum number of controlled clients	32
Maximum number of parental control policies	32
Selecting clients from the client list to block their access to the Internet	Yes
Specifying MAC addresses of controlled clients	Yes
Ethernet Interface	

Software Specifications

Model	RG-EW1800GX PRO
MAC address cloning	Yes
VLAN-based IPTV	Yes
Flow Control	
Flow control based on number of users	Yes
Standalone/Shared mode	Yes
Interface flow control	Yes
Multicast	
IGMP proxy	Yes
IGMP snooping	Yes Note: Not supported by wired connections when IPTV is turned on
IPTV/VLAN	
Multiple IPTV ports	Yes
WLAN	
1024-QAM	Yes
OFDMA	Yes (DL OFDMA)
MLO	No
DFS	Yes
802.11k/v roaming	Yes
Wi-Fi blocklist capacity	64
SSID hiding	Yes

Software Specifications

Model	RG-EW1800GX PRO
Beamforming	Yes
Wireless Configuration	
Guest Wi-Fi	Yes
System Performance Capacity	
Recommended number of concurrent clients	12 (2.4 GHz)
	36 (5 GHz)
IPTV/IGMP client capacity	5
IPTV/IGMP multicast capacity	5
IPTV/IGMP wired forwarding performance	20 Mbps
Recommended camera limit	6 (2.4 GHz)
	16 (5 GHz)
Rate Limiting	
Client-based rate limiting	Yes
Security	
Encryption mode	WPA-PSK, WPA2-PSK, WPA/WPA2-PSK, WPA3-SAE, WPA2-PSK/WPA3-SAE
Network Management and Monitoring	
Line detection	Yes
Arabic	Yes
Chinese (Hong Kong Traditional)	Yes

Software Specifications

Model	RG-EW1800GX PRO
Chinese (Simplified)	Yes
English	Yes
Indonesian	Yes
Italian	Yes
Russian	Yes
Spanish (Latin America)	Yes
Thai	Yes
Turkish	Yes
Vietnamese	Yes
Ruijie Cloud management	Yes
Scheduled device restart	Yes
eWeb login password length	8 to 63 characters
Wired repeater mode	Yes
Wireless repeater mode	Yes
WISP mode	Yes
User agreement signing	Yes
Reyee Mesh 3.0	
Reyee Mesh 3.0	Yes
Automatic switching between wired and wireless repeater mode	Yes
Recommended hop count	2

Software Specifications

Model	RG-EW1800GX PRO
Maximum number of clients	192
Maximum number of devices	32
SIM Card Management	
Batch import of APN configurations	No
Number of APN configurations for batch import	No
VPN	
Number of concurrent tunnels supported by the OpenVPN server	8
Certificate authentication	Yes
OpenVPN bandwidth	13 Mbps
OpenVPN client	Yes
OpenVPN server	Yes
Server domain name configuration	Yes
Username and password authentication	Yes
Number of concurrent tunnels supported by the PPTP VPN server	30
PPTP VPN client	Yes
PPTP VPN server	Yes

Package Contents

Model	RG-EW1800GX PRO
Manual	
User Manual	1
Warranty Card	1
Accessories	
Ethernet cable	1
Power adapter	1
Device	
Device	1

Ruijie | ReYee

 **R**edefine **y**our **e**asy network



Ruijie Networks Co., Ltd.

Official Website: <https://Reyee.Ruijie.com>